PRODUCT INTRODUCTION

It is a high performance track light designed for museum, art gallery or other places. Its outstanding high color rende index 97 can reflect the real color and present the perfect texture of the items on display.

SPECIFICATION

Wattage : 9W / 12W
Color temperature : 2700K / 3000K / 4000K
CRI : Ra97（R9>90)
Beam angle : 15° / 24° / 36°
Adjusted by zoom lens control device
Driver : Input voltage AC220V-240V, PF>0.9
Dimming : 0/1-10V , DALI, TRIAC , CASAMBI

FEATURES

Product surface color : Silver, Black, Customized
Rotatable through 365° on adaptor, 90° tilt
Adaptor : 3-circuit / ceiling-mounted
Protection degree : IP20 (En60598)
Energy efficiency: EEIA

Radial distribution & Conical illuminance

D Distance To Fix From Wall or Floor
LX Initial illuminance Level At Center of Bram
L Beam Length(where candlepower drops to 50% of maximun)
W Beam Width(where candlepower drops to 50% of maximun)

Radial distribution & Conical illuminance

Specifications

Model No.	Total Power (W)	LED Power (W)	Voltage	CRI (Ra)	Corlor Temp (K)	LED Flux (lm)	Beam Angle	IP Grade
Patenon AE06	9	8.1	AC220V-240V	97	2700	900	15° / 24° / 36°	IP20
					3000	963		
					4000	990		
Patenon AE06	12	10.8			2700	1200		
					3000	1284		
					4000	1320		

· Thermally stable typical lumens (±10%)

Package information

Model No.	Packaging/Unit	Pieces/Unit	Dimensions (L x W x H)	Gross Weight	Volume
Patenon AE06	Inner box	1	220x120x120mm	0.40kg	3.17dm³
	Outer box	12	630x240x510mm	11.00kg	77.11dm³

Optional accessories

Color coated lens

Honeycomb louver

Ceiling adapter